



## Press release

### **HA 120 PX - Rough terrain articulating boom**

Placing the client and innovation at the core of the company's mission, has enabled, the number 3 manufacturer of aerial work platforms in the world, to develop a complete range of more than 60 models.

This drive to innovate gives rise to numerous new machines every year and makes Haulotte Group the specialist of people and material lifting equipments.

Among these new models is the articulating boom **HA 120 PX**: designed to meet the needs of working at heights of 12 m, this model is particularly suited to maintenance work and offers many benefits.

➤ **Optimal productivity**

Up to 4 simultaneous and proportional movements, the HA120 PX boom reaches the maximum height within 30 seconds.

With a wide basket of 1.50m (4ft 11in) as standard equipment, offering a maximum capacity of 230 kg, and fitted with a Load Managing System, the articulated boom HA 120 PX also offers an ergonomic and user friendly control panel, already very popular on the HA16PX.

➤ **Outstanding rough terrain driving features**

The HA 120 PX is fitted with simultaneous 4 wheel drive and steer as standard, a 26cm (11in) ground clearance and a hydraulic differential lock system give exceptional all-terrain performance with a gradeability up to 45%. This allows easy access in difficult working areas and rough terrain conditions.

➤ **Excellent manoeuvrability in the tightest spaces**

Its narrow turning radius (3.85m – 12ft 8in), combined with the zero tailswing give to the HA 120PX superb manoeuverability whatever the working environment. Dual parallelogram riser allows ascent and descent along a vertical plane without retraction or extension of the boom, which offers comfort and maximum productivity.





➤ **Large horizontal outreach allied to a capacity of remarkable overhang**

Due to the horizontal outreach of 6.60m ((21ft 8in) and its up and over clearance of 5.70m (18ft 8in), the HA 120PX can easily by-pass the obstacles, and cover a big working envelope.

The narrow turning radius, the vertical jib rotation (140 °) and the platform rotation in 180 ° facilitate use of the machine in any the work ing environment.

Tilt controller (up to 5°), automatic platform leveling, mechanical turret slewing hook, resistance in winds up to 45km/h (28mph) and towing hooks and lifting eyes are additional features to benefit the user.

Offering maximum profitability and safety, the platforms **HA 120 PX** meets the requirements of the latest labour regulations, and also meets European standards (CE marking, EN 280).

**Contact Presse:**

**Haulotte Group – Carine PLOTON**

Tel : 0033 4 77 29 94 86 – e-mail : [cploton@haulotte.com](mailto:cploton@haulotte.com)

Website : [www.haulotte.com](http://www.haulotte.com)

